

Role of prefabricated systems in massive Low Energy Renovation of Building


Mark Zimmermann
Empa




How much energy do we really need ?



Maslow Pyramide




Countries with Highest CO2 Emissionen per Capita




Source: UN Scientific Expert Group Report on Climate Change and Sustainable Development

Countries with Highest CO2 Emissionen per Capita




Source: UN Scientific Expert Group Report on Climate Change and Sustainable Development

Countries with Largest Negative Climate Impact




Source: UN Scientific Expert Group Report on Climate Change and Sustainable Development

Losers and Winners



Source: UN Scientific Expert Group Report on Climate Change and Sustainable Development

Global CO₂-Concentration




Source: Dr. Pieter Tans, NOAA/ESRL (<http://www.esrl.noaa.gov/gmd/ccgg/trends/>)

The 2000 Watt Concept

- About 2'000 Watt per capita (17'500 kWh/a) are needed, to ensure a healthy society that achieves a reasonable level of prosperity
- In order to achieve also the goals of IPCC (Intergovernmental Panel for Climate Change) of 1 ton CO₂-emissionen per capita, only 500 W may come from fossil fuels, 1'500 W have to come from renewable, CO₂-free energy resources.



Aimed Distribution of Energy



Source: Novatlantis, www.novatlantis.ch

Passive Houses fulfil 2000 Watt-criteria


- Max. Heating load $< 10 \text{ W/m}^2$
- Heating power $< 10 \text{ kWh}/(\text{m}^2 \cdot \text{a})$
- Air leakage of envelope $n_{L50} < 0.6 \text{ /h}$
- Efficient, electrical appliances (A label)

About 30'000 housing units
built in D, A, CH




Efficiency Curve of Buildings

From 15 to 1 L/m² for heating



Heating Demand of Building Stock

Heating Energy Demand and Heated Floor Area of Dwellings in Zurich



What is an optimal renovation strategy?

Repair

–

Renewal

–

Demolition ?



Renewal or Reconstruction?

		Potential for extension		
		small ≈ 0 %	medium ≈15 %	large >25 %
Location	attractive	Renewal	Renewal evtl. Reconstruction	Reconstruction
	medium	Renewal Repair	Renewal	Renewal evtl. Reconstruction
	poor	Repair	Repair	Repair evtl. Reconstruction

... also to be considered

- Usability / flexibility / Demand
- Construction quality, sound protection, earthquake safety
- Integration in neighborhood, historic value
- Tenant situation

Deep Building Renovation


Building renewal with prefabricated elements

80-90 % energy savings + added values (room extension, attic apartment)




Traditional Renovation

- hardly future oriented
- too many technical compromises
- too many craftsmen involved
- poor coordination on site
- low quality level
- inefficient construction processes



Prefab Building Renovation


- Whole building concept
- no technical compromises
- few companies involved
- well coordinated modules
- quality assurance
- rapid construction processes



Prefab Building Renovation

SOLTAG

VELUX®



Prefab Building Renovation



Soltag project by Velux, Copenhagen Denmark




Austrian Façade Elements



Large size modules developed by Austrian team

Swiss Façade Elements



Small size modules
developed by Swiss
team


French Façade Elements



Large size prefabricated steel frame retrofit modules

Challenge of Pre-Fabrication

Prefabrication of large elements has to ensure that the elements will fit to the existing building




Picture: Wood-
Wisdom, TES-
EnergyFaçade




Mounting the pre-fabricated roof structure
calls for precision. And new ideas.

Laser Scanning – Design Support




Planarity of façades



Horizontal sections

Planning of Façade Modules





CYCLE DE FORMATION ENERGIE-ENVIRONNEMENT 2015/2016

Prefabrication of Façade Elements



CYCLE DE FORMATION ENERGIE-ENVIRONNEMENT 2015/2016


Mounting of Façade Elements





IEA Demonstration Buildings

- Demonstration projects in Austria, Netherlands, Switzerland
- 6 Demonstration sites with totally 363 apartments and 1 school



Austrian Demonstration Buildings

Renovation of 3 apartment buildings (1959) completed 2008,
GAP-Solution / AEE INTEC



Austrian Demonstration Buildings

Renovation of 2 apartment buildings (1970) completed 2009,
GAP-Solution / AEE INTEC



Austrian Demonstration Buildings

Renovation of row houses buildings (1952) completed 2009,
GAP-Solution / AEE INTEC



Swiss Demonstration Buildings

Renovation of apartment building (1952) completed 2009,
Miloni Architects



Swiss Demonstration Buildings

Renovation of apartment building (1952) completed 2009,
Beat Kaempfen Architects



Swiss Demonstration Buildings

Renovation of school building (1952) completed 2011,
Bruno Thoma / Alexander Ritz



Dutch Demonstration Buildings

Renovation of residential area by DAT architecten / Trecodome



E2ReBuild



Start Building Finances Repair Retrofit Reconstruction Results End

start

Project name

Address

Author

Date 2015-10-22

Country



Simple, detached suburban apartment building, constructed about 1930. Simple to average standard, relatively small apartments, normally 3 stories, raised ground floor, massive wall construction, artificial stone reveals, overhanging balconies, roof space not or little used as living space, simple staircase without elevator.


← back

next →

European Retrofit Advisor



**Actual
state**



Society



Environment




Economy

Retrofit Advisor

Description of reference building



Building type 1:
Simple, detached suburban apartment building, constructed about 1930
Simple to average standard, relatively small apartments, normally 3 stories, raised ground floor, massive wall construction, artificial stone reveals, overhanging balconies, roof space not or little used as living space, simple staircase without elevator.



* Indicative, no official label


Information about your own building

Default values of the selected building type will be used for missing information. The more information you can give, the more precise the evaluation will be.


Building data

Heated floor area	m²	380
Unheated floor area	m²	165
Room height (in apartments)	m	2.45
Floors (ground floor and above)	Number	3.0
Elevator	yes/no	no
Plot size	m²	680


Market value €



Description of reference building



Building type 1:
Simple, detached suburban apartment building, constructed about 1930
Simple to average standard, relatively small apartments, normally 3 stories, raised ground floor, massive wall construction, artificial stone reveals, overhanging balconies, roof space not or little used as living space, simple staircase without elevator.



* Indicative, no official label


Information about your own building

Default values of the selected building type will be used for missing information. The more information you can give, the more precise the evaluation will be.

Building data

Heated floor area	m²	540
Unheated floor area	m²	186
Room height (in apartments)	m	2.45
Floors (ground floor and above)	Number	4.0
Elevator	yes/no	no
Plot size	m²	650

Market value €



Retrofit Advisor

Actual State

Standard renovation

SIA standard
Minergy
Minergie-P
Retrofit

New balconies
Steep roof attic
Flat roof attic
Room extension

1.2 Renovation of building envelope according to Minergie-standard:
Compact façade insulation 200mm, window replacement $U=1.1 \text{ W/m}^2\text{K}$, insulation of roof space and basement (ceiling), installation of a mechanical ventilation system with heat recovery, renovation of interior


Energy Label*

	Actual-state	Repair	Retrofit	Reconstruction
efficient			A 49%	A 39%
A				
B				
C		C 146%		
D	D 172%			
E				
F				
G				
less efficient				
Global warming potential	E	D	C	A
Heating energy demand	E	D	A	A
Renewable energies	0%	0%	0%	35%



* Indicative, no official label

European Retrofit Advisor

Prefab Retrofit with Room Extension



European Retrofit Advisor



Historical Buildings



**Traditional
buildings should be
refurbished with
traditional methods**

New Insulation Rendering



About 85% nanoporous aerogel granulate is used as additive for the light weight plaster




Mineral rendering that is insulating like air

New Insulation Rendering

- Thermal conductivity $< 30 \text{ mW} / (\text{m} \cdot \text{K})$ in real application
- 60 – 80 mm thickness of one layer
- Sprayable with available rendering machines
- Vapour resistance $\mu < 5$
- Purely mineral
- Low shrinkage
- Applicable in- and outside




Spraying of Aerogel Renderings



High pressures of approx. 8 bar press free water into the aerogel pores. If this happens, the thermal conductivity will increase rapidly.

Thermal Conductivity of Insulation Renderings

Thermal conductivity of insulating rendering systems in $\text{mW}/(\text{m}\cdot\text{K})$





Summary Prefab Building Retrofit

- Prefab Retrofit suitable for deep renovation
- Energy savings > 80% are realistic target, potential for Zero or Plus-energy building
- Energy savings measures itself are hardly cost effective > added values needed
- Expected service life > 50 years
- Technologies are available

Social challenges for energy retrofit

- Financing situation for building renovation often difficult
- Additional legal requirements for comprehensive renovations (earthquake, fire, sound, energy, water management, electrical installations)
- Trend to self-owned apartments with emphasis on internal and step by step renovations
- Additional difficulties for inhabited construction sites, especially during winter time



Thank you for your attention!

www.empa-ren.ch/A50.htm

www.empa-ren.ch/ccem-surhib.htm

www.era.empa.ch